

	1912		1912
RECOMMENDED MINIMUM PTO HP	35 HP (GEAR DRIVE TRANS)	CUT WIDTH	144"
HITCH	SWIVEL CLEVIS	OVERALL WIDTH	151"
DECK THICKNESS	10 GAGE	OVERALL LENGTH W/WHEELS	158"
DECK HEIGHT	11"	TONGUE WEIGHT	759 LBS
SIDE SKIT MATERIAL	3/16'	OVERALL WEIGHT	2630 LBS
HINGE RODS	1"	CUT HEIGHT	1-1/2"-12"
SUSPENSION	SINGLE SPRING	CUTTING CAPACITY	UP TO 2"
OUTBOARD GEARBOX PWR RATING	75 HP	INPUT PTO	ASAE CAT 5 CONSTANT VELOCITY
SPLITTER GEARBOX PWR RATING	175 HP	WING DRIVE PTO	ASAE CAT 4 w/SLIP CLUTCH
GEARBOX RPM	540 RPM	SKID SHOES	REPLACEABLE
BLADES	1/2" X 3" w/LIFT	CHAIN SHIELDS	SINGLE ROW CHAIN SHIELDS STANDARD
BLADE TIP SPEED	15,657 FPM	TOWING SAFETY CHAIN	STANDARD
BLADE OVERLAP	6"	GEARBOX WARRANTY	5 YR LIMITED
BLADE CARRIERS	3/16' FORMED PLATE W/ 3/4" x 20" BLADE BAR	WHEEL TYPE	5 LUG LAMINATED STD-USED AIRCRAFT TIRES OPTIONAL